

AQL-910 Controllers

AQL-910-PSU-50

- Up to 50W
- Input Voltage: 90-264VAC, 50~60Hz
- Power Output: 1 way(RJ45) x 24VDC, 340±10mA
- 20 built-in fixed colors & 9 built-in fade effects
- 3 channel (RGB) and 5 channel (RGB, dimmer, strobe)
- Master/ Slave Function & Delay Start (Flicker Free)
- USITT DMX 512-A address setting
- Dimensions L248 x W84 x H75



AQL-910-PSU-100

- Up to 100W
- Input Voltage: 90-264VAC, 50~60Hz
- Power Output: 4 way(RJ45) x 24VDC, 340±10mA
- 20 built-in fixed colors & 9 built-in fade effects
- 3 channel (RGB) and 5 channel (RGB, dimmer, strobe)
- Master/ Slave Function & Delay Start (Flicker Free)
- USITT DMX 512-A address setting
- Dimensions L280 x W175 x H65



AQL-910-PSU-200

- Up to 200W
- Input Voltage: 90-264VAC, 50~60Hz
- Power Output: 4 way(RJ45) x 24VDC, 340±10mA
- 20 built-in fixed colors & 9 built-in fade effects
- 3 channel (RGB) and 5 channel (RGB, dimmer, strobe)
- Master/ Slave Function & Delay Start (Flicker Free)
- USITT DMX 512-A address setting
- Dimensions L295 x W220 x H73



AQL-910-CTL-ETC-5B

- Power on/off
- 9 pre-set static colors
- 4 effect modes
- Speed adjustment
- Luminance adjustment
- Channel setting in group and independently
- Power Requirement: 12VDC
- Dimensions (mm):ETC-P (L116xW120xH24) / ETC-B (L82xW74xH24) Weight: 0.2Kg

